




NorBreeze ISLA CUBE GLASS 60 WH

Cod. 8565

EAN 8435025785656



GENERAL INFORMATION

EAN/UPC	8435025785656
Subfamily	Island

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	30
EI class (energy efficiency class)	A
FDE (fluid dynamic efficiency)	34,7
FDE class (fluid dynamic efficiency class)	A
LE (light efficiency) (lux/W)	36,6
LE class (light efficiency class)	A
GFE (grease filtering efficiency)	91,2
GFE class (grease filtering efficiency class)	B
Airflow in normal mode MIN (m3/h)	200
Airflow in normal mode MAX (m3/h)	645
Airflow in boost mode MIN (m3/h)	820
Acoustic power in normal mode MIN (dB)	42
Acoustic power in normal mode MAX (dB)	66
Acoustic power boost mode (dB)	69
Po (energy consumption in off mode) (W)	0,41
Ps (energy consumption in standby mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	0,8
EI (Energy Efficiency Index)	47,9
QBEP (maximum efficiency at air flow point) (m3/h)	363,7
PBEP (maximum efficiency at pressure point) (Pa)	248
WBEP (power consumption at maximum efficiency) (W)	74,8
WL (nominal power lighting system) (W)	14
EMIDDLE (Average illuminance on the cooking surface) (lux)	513

External Dimensions

Width (mm)	620
Depth (mm)	480
Maximum total height (mm)	1140
Minimum total height (mm)	815
Diamètre de sortie (mm)	150, 125

Characteristics

Motor quantity	1
Motor model	BTDCA
Maximum pressure (Pa)	455
Filter technology	Aluminium mesh
Control technology	Electronic Touch Control
Booster	√
Power levels	5
Timer	√
Filter saturation indicator	√
Charcoal filter replacement indicator	-
Dimmer function	√
Connectivity	-
Remote control	-
Display	Display_grafico

Lighting

Light model	ECOLED 2
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	650
Minimum distance to gas plate (mm)	650
Recirculation option	√
Charcoal filter	-
Back draught shutter	Included
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Nominal input power (W)	144
Electric shock protection	Class II

Accessories

Upper decorative duct extension	No
White decorative duct	No
Black decorative duct	No
Island tube booster	No
MAX PRO Metal filter	2800917
Activated charcoal filter	2859392
Noiseless flexible duct	2893002
Recirculation kit	No